



Modular Adsorption Dryers

Highly efficient air treatment



Innovative compressed air treatment

A-Series

Totally dry and clean air

The A-Series modular compressed air dryers - a dedicated solution for every application

By combining the proven benefits of desiccant drying with modern design, CompAir provides an extremely compact and reliable system to totally dry and clean compressed air.


At the heart of any compressed air treatment solution is the dryer, it's purpose, to remove water vapour, stop condensation, corrosion and in the case of adsorption dryers, inhibit the growth of micro-organisms.

The CompAir A-Series of heatless regenerative adsorption dryers have proven to be the ideal solution for many thousands of compressed air users worldwide in a wide variety of industries.

Why chose adsorption dryer technology?

Compressed air purification must deliver uncompromising performance and reliability whilst providing the right balance of air quality with lowest cost of operation.

Heatless adsorption dryers, which are also known as PSA dryers, are the simplest type of adsorption dryer available and have long been the dryer of choice for many industries and applications. They are simple, reliable and cost effective and for small to medium flow systems, often the only viable technology available. Additionally, modular heatless dryers such as the A-Series provide an even more reliable, smaller, more compact & lightweight dryer which can be installed in both, the compressor room or at the point of use.



“Clean, dry air improves production efficiency and reduces maintenance costs and downtime. Adsorption dryers provide the highest levels of dry compressed air.”

A-Series Product Overview

A1LX to A7LX Series

Flowrates from 0.9 m³/min



A7XS to A50XS Series

Flowrates from 0.68 m³/min



A68XS to A340XS Series

Flowrates from 6.8 m³/min



How it works

Adsorption dryers work on the principle of moisture always migrating to the driest medium possible. Therefore, water vapour is removed from compressed air by passing it over an adsorbent desiccant material.

As the air contacts the adsorbent material, water vapour transfers from the wet air to the dry desiccant, however, adsorbent materials have a fixed adsorption capacity and once this capacity is reached, they must be regenerated or replaced. Therefore, to provide a continuous supply of clean, dry compressed air, adsorbent dryers utilise two chambers of desiccant material and at any one time, whilst one chamber is on-line, drying the incoming compressed air, the other is either off-line, being regenerated or is re-pressurised, ready to come on-line. All adsorption dryers remove water in this manner.

The energy consumed by an adsorption dryer can be directly attributed to the method used to regenerate the adsorbent material. The CompAir A-Series dryers utilise the Heatless PSA method to regenerate the adsorbent material.

The benefits of heatless adsorption dryers:



- ▶ Robust and reliable industry proven design
- ▶ Suitable for all industries and applications. Some adsorption dryer regeneration methods prevent their use in certain industries/applications.
- ▶ Lower capital investment and reduced complexity compared to other adsorption dryer regeneration methods
- ▶ Lower maintenance costs in comparison to other adsorption dryer regeneration methods
- ▶ No heat, heaters or heat related issues

Improving manufacturing efficiency

Drying cycle

The process air enters the dryer through the inlet and is directed into the on-line drying chamber via the inlet valves and lower manifold.

The air is evenly distributed through the drying columns and passes over the desiccant material, reducing the water vapour content. The dried process air then combines in the upper manifold and exits the dryer via the outlet check valves.



Column changeover

Before the on-line (drying) and off-line (regenerating) columns change over, the dryer exhaust valve, is closed, allowing the purge air to re-pressurise the off-line columns. This ensures a consistent system pressure and dewpoint when the drying chambers change over.




Regeneration cycle (Heatless PSA)

At the start of the regeneration cycle, the exhaust valve of the dryer is closed and the off-line chamber is at full line pressure. The air in the off-line chamber has dewpoint equal to the air leaving the dryer.

The exhaust valve is then opened and the dry air within the chamber expands rapidly as it leaves the dryer via the exhaust silencer, forcing water to be removed from the desiccant material.

Once the off-line chamber has de-pressurised, a continuous bleed of dried process air is directed into the off-line upper manifold. This air is known as purge air. With the exhaust valve open, the purge air expands from line pressure to atmospheric pressure and flows downwards through the columns, over the off-line desiccant material. As the purge air at line pressure contains a fixed amount of water vapour, allowing it to expand means the purge air becomes even drier, increasing its capacity to remove water from the saturated desiccant bed.



Four key features guarantee air quality

CompAir filtration

Adsorption dryers are designed for the removal of water vapour and not liquid water, water aerosols, oil, particulates or micro-organisms. Only by using CompAir pre and after filtration can the removal of these contaminants be assured and air quality in accordance with all editions of ISO8573-1 be guaranteed.

Modular aluminium design

Aluminium extrusions are used throughout for drying chambers and distribution manifolds. This design allows the desiccant material to be retained within the drying chambers. 'Snowstorm' filling, prevents movement of the desiccant material during operation and also eliminates desiccant attrition and breakdown which could lead to a loss of pressure dewpoint.



Adsorption desiccant material

- Optimum adsorption and regeneration capacity
 - > to ensure consistent dewpoint
- Low dusting
 - > to prevent blockage of downstream filtration
- High crush strength
 - > to prevent breakdown of the desiccant during operation
- High resistance to aggressive and oil-free condensate
 - > for compatibility with all types of air compressor, their lubricants and condensate

CompAir air treatment


The 'Snowstorm' filling method

Utilised across the CompAir modular dryers is the snowstorm filling technique used to charge the drying chambers with adsorbent desiccant material.

- Achieves maximum packing density for the desiccant material, fully utilising all of the available space envelope
- Prevents air channelling through the desiccant as experienced with twin tower designs. Due to channelling, twin tower designs require more desiccant to achieve an identical dewpoint increasing physical size, operational and maintenance costs
- Prevents desiccant attrition which can lead to dusting, blocked filters and loss of dewpoint
- Allows 100% of the available desiccant material to be used for drying, therefore reducing the amount of desiccant required and maintenance costs
- 100% of the desiccant is regenerated ensuring consistent dewpoint
- Provides a low, equal resistance to air flow allowing multiple drying chambers and multiple dryer banks to be used, a feature available with the A-Series from CompAir




Snowstorm filling



Snowstorm filled bed

Consistent drying with no desiccant attrition



Loose filled bed

Inconsistent drying and desiccant attrition

The 'Snowstorm' filling technique ensures consistent dewpoint performance

Energy savings with dewpoint dependent switching (DDS) energy management system

The energy required to regenerate the off-line desiccant bed in an adsorption dryer is constant, and based upon the assumption that the dryer is operating at its full capacity and the desiccant bed requiring regeneration has been fully saturated. In reality, a dryer is rarely operating at full capacity all of the time, for example during shift work and periods of low demand. Daily and seasonal fluctuations in ambient temperature and humidity also change the moisture loading placed upon the dryer.

Under such conditions, at the point in the drying cycle where the air flow is switched from one drying chamber to the other, there is the potential for drying capacity to remain in the desiccant material about to undergo regeneration. As the energy used to regenerate this partially saturated bed is based upon the assumption that the bed is fully saturated, more energy (purge air) is consumed than is actually necessary.

DDS Operation - Energy Saving Cycle (Heatless Dryer example shown)

Time [Minutes]	DDS Drying / Regeneration Cycle							
	0	2.5	3	Changeover time dictated by outlet dewpoint	0	2.5	3	Changeover time dictated by outlet dewpoint
Side A	Regeneration	Re-pressurisation	Energy Saving	Changeover	Drying			Changeover
Side B	Drying				Regeneration	Re-pressurisation	Energy Saving	

DDS Energy Saving (Heatless Dryer example shown)

Air Demand %	Energy Saving %	Energy Saving	Environmental Saving
		P/A kW	P/A Kg CO ₂
100	33.00	95,040	50,371
90	40.00	115,200	61,056
80	47.00	135,360	71,741
70	53.00	152,640	80,899
60	60.00	172,800	91,584
50	66.00	190,080	100,742

System pressure 6 bar g. Max Temp 35°C. System flow 1700 m³/hr (1000 cfm). Average pressure 6.5 bar g. Average Temp 30°C.



Technical data

A Series A1LX - A7LX

Product Selection

Model	Pipe Size	Inlet Flowrates			
		[m ³ /min]	[m ³ /hr]	[L/S]	[cfm]
A1LX	3/8"	0.09	5.1	1	3
A2LX	3/8"	0.14	8.5	2	5
A3LX	3/8"	0.23	13.6	4	8
A4LX	3/8"	0.28	17.0	5	10
A5LX	3/8"	0.37	22.1	6	13
A6LX	3/8"	0.43	25.5	7	15
A7LX	3/8"	0.57	34.0	9	20



Stated flows are for operation at 7 bar g (100 psi g) with reference to 20°C, 1 bar a, 0% relative water vapour pressure. For flows at other pressures, apply the correction factors shown.

Dryer Performance

Dryer Models	*Dewpoint [Standard]		ISO8573-1:2010 Classification [Standard]	*Dewpoint [Option 1]		ISO8573-1:2010 Classification [Option 1]
	[°C]	[°F]		[°C]	[°F]	
A_LX	-40	-40	Class 2	-70	-100	Class 1

Technical Data

Dryer Models	Min Operating Pressure		Max Operating Pressure		Min Inlet Temperature		Max Inlet Temperature		Max Ambient Temperature	
	[bar g]	[psi g]	[bar g]	[psi g]	[°C]	[°F]	[°C]	[°F]	[°C]	[°F]
A_LX	4	58	12	175	2	35	50	122	55	131

Dryer Models	Electrical Supply [Standard]	Electrical Supply [Optional]	Thread Connection	Noise Level [Average]	Electronic Controller Options	Function	
	Tolerance ± 10%	Tolerance ± 10%		[dB[A]		Power On Indication	Service Interval Indication
A_LX	230 / 1ph / 50Hz	115 / 1ph / 60Hz	BSPP or NPT	<75	A_LX	•	•

For fully pneumatic applications, a A_LX Series MINI range is available. Please contact CompAir for further information.

Correction Factors

Temperature Correction Factor CFT							
Maximum Inlet Temperature	[°C]	25	30	35	40	45	50
	[°F]	77	86	95	104	113	122
	CFT	1.00	1.00	1.00	1.04	1.14	1.37

Pressure Correction Factor CFP											
Minimum Inlet Pressure	[bar g]	4	5	6	7	8	9	10	11	12	
	[psi g]	58	73	87	102	116	131	145	160	174	
	CFP	1.60	1.33	1.14	1.00	1.03	0.93	0.85	0.78	0.71	

Dewpoint Correction Factor CFD			
Required Dewpoint		Standard	Option 1
	PDP °C	-40	-70
	PDP °F	-40	-100
CFD	1.00	1.43	

Weights and Dimensions

Model	Pipe Size	Dimensions						Weight	
		Height [H]		Width [W]		Depth [D]		[Kg]	[lbs]
		[mm]	[ins]	[mm]	[ins]	[mm]	[ins]		
A1LX	3/8"	422	16.6	289	11.4	149	5.9	11	24.2
A2LX		500	19.7					13	28.7
A3LX		616	24.2					16	35.3
A4LX		692	27.2					18	39.7
A5LX		847	33.3					20	44.1
A6LX		906	35.7					23	50.7
A7LX		1098	43.2					28	61.7

Recommended Filtration

Model	Filter Pipe Size BSPT or NPT	Inlet General Purpose Pre-filter	Inlet High Efficiency Filter	Outlet Dust Filter
A1LX	3/8"	CF0006G3/8"G	Built into dryer	Built into dryer
A2LX				
A3LX				
A4LX				
A5LX				
A6LX				
A7LX				

*A_LX dryers include integral high efficiency pre and general purpose dust filters.

A7XS - A50XS

Product Selection

Model	Pipe Size	Inlet Flowrates			
		[m ³ /min]	[m ³ /hr]	[L/S]	[cfm]
A7XS	3/4"	0.68	41	11	24
A9XS		0.91	55	15	32
A12XS		1.19	71	20	42
A15XS		1.50	90	25	53
A18XS		1.84	110	31	65
A25XS		2.49	149	42	88
A30XS	1"	3.01	180	50	106
A37XS		3.69	221	61	130
A50XS		4.99	299	83	176



Stated flows are for operation at 7 bar g (100 psi g) with reference to 20°C, 1 bar a, 0% relative water vapour pressure. For flows at other pressures, apply the correction factors shown.

Dryer Performance

Dryer Models	Dewpoint [Standard]		ISO8573-1:2010 Classification [Standard]	Dewpoint [Option 1]		ISO8573-1:2010 Classification [Option 1]
	[°C]	[°F]		[°C]	[°F]	
A7XS - A50XS	-40	-40	Class 2	-70	-100	Class 1

Technical Data

Dryer Models	Min Operating Pressure		Max Operating Pressure		Min Operating Temperature		Max Operating Temperature		Max Ambient Temperature		Electrical Supply [Standard]	Electrical Supply [Optional]	Thread Connection	Noise Level [dB(A)]
	[bar g]	[psi g]	[bar g]	[psi g]	[°C]	[°F]	[°C]	[°F]	[°C]	[°F]				
A7XS - A50XS	4	58	16	232	5	41	50	122	55	131	230V 1ph 50/60Hz	110V 1ph 50/60Hz	BSPP or NPT	<75
A30XS - A50XSDS			13	190										

Controller Options

Controller Options	Function								
	Power On Indication	Fault Indication	Display Fault Condition Values	Service Interval Indication	Service Countdown Timers	Configurable Alarm Settings	Remote Volt Free Alarm contacts	Filter Service Timer	DDS Energy Management System
A7XS - A50XS (Electronic Control)	•	•					•		•
A7XSDS - A50XSDS									

*ATEX compliant option available. For hazardous environments, a fully pneumatic ATEX compliant version of A_XS Series is available. ATEX Directive 94/9/EC, Group II, Category 2GD, T6.

Correction Factors


Temperature Correction Factor CFT							
Maximum Inlet Temperature	[°C]	25	30	35	40	45	50
	[°F]	77	86	95	104	113	122
	CFT	1.00	1.00	1.00	1.04	1.14	1.37

Pressure Correction Factor CFP														
Minimum Inlet Pressure	[bar g]	4	5	6	7	8	9	10	11	12	13	14	15	16
	[psi g]	58	73	87	100	116	131	145	160	174	189	203	218	232
	CFP	1.60	1.33	1.14	1.00	0.89	0.80	0.73	0.67	0.62	0.57	0.54	0.50	0.47

Dewpoint Correction Factor CFD		Standard	Option 1
Required Dewpoint	PDP °C	-40	-70
	PDP °F	-40	-100
	CFD	1.00	1.43

Weights and Dimensions

Model	Pipe Size Inlet / Outlet	Dimensions						Weight	
		Height [H]		Width [W]		Depth [D]		[kg]	[lbs]
		[mm]	[ins]	[mm]	[ins]	[mm]	[ins]		
A7XS	¾"	837	33.0	284	11.2	302	11.9	32	70
A9XS		1003	39.5					37	81
A12XS		1168	46.0					42	92
A15XS		1333	52.5					47	103
A18XS		1499	59.0					52	114
A25XS		1747	68.8					60	132
A30XS	1"	1433	56.4	220	8.7	566	22.3	80	176
A37XS		1599	63.0					90	198
A50XS		1847	72.7					104	229



Recommended Filtration

For Dryer Model	Filter Pipe Size BSPT or NPT	Inlet General Purpose Pre-filter	Inlet High Efficiency Filter	Outlet Dust Filter
A7XS	¾"	CF0018G¾"G	CF0018G¾"H	CF0018G¾"G
A9XS				
A12XS				
A15XS				
A18XS				
A25XS				
A30XS	1"	CF0036G1"G	CF0036G1"H	CF0036G1"G
A37XS		CF0066G1"G	CF0066G1"H	CF0066G1"G
A50XS				

Inlet High Efficiency Filter and Outlet Dust Filter are included with these dryers as standard.

A068XS - A340XS

Product Selection

	Model	Pipe Size	Flowrates			
			[m³/min]	[m³/hr]	[L/S]	[cfm]
Single Bank	A068XS	2"	6.81	408	113	240
	A102XS		10.22	612	170	360
	A127XS		12.78	765	213	450
	A170XS		17.03	1020	283	600
	A212XS	2½"	21	1275	354	750
	A255XS		26	1530	425	900
	A297XS		30	1785	496	1050
	A340XS		34	2040	567	1200
Multi-Bank	2 x A212XS	G 2½"	43	2550	708	1500
	2 x A255XS		51	3060	850	1800
	2 x A297XS		60	3570	992	2100
	2 x A340XS		68	4080	1133	2400
	3 x A255XS		77	4590	1275	2700
	3 x A297XS		89	5355	1488	3150
	3 x A340XS		102	6120	1700	3600



Stated flows are for operation at 7 bar g (100 psi g) with reference to 20°C, 1 bar a, 0% relative water vapour pressure. For flows at other pressures apply the correction factors shown.

Dryer Performance

Dryer Models	Dewpoint [Standard]		ISO8573-1:2010 Classification [Standard]	Dewpoint [Option 1]		ISO8573-1:2010 Classification [Option 1]	Dewpoint [Option 2]		ISO8573-1:2010 Classification [Option 2]
	[°C]	[°F]		[°C]	[°F]		[°C]	[°F]	
A068XS - A340XS	-40	-40	Class 2	-70	-100	Class 1	-20	-4	Class 3

Technical Data

Dryer Models	Min Operating Pressure		Max Operating Pressure		Min Operating Temp		Max Operating Temp		Max Ambient Temp		Electrical supply [Standard]	Electrical supply [Optional]	Thread Connections	Noise Level [dB(A)]
	[bar g]	[psi g]	[bar g]	[psi g]	[°C]	[°F]	[°C]	[°F]	[°C]	[°F]				
AX_S AX_E	4	58	13	190	5	41	50	122	55	131	85 - 265 V 1ph 50/60Hz	N/A	BSPP or NPT	<75

Controller Options

Controller Options	Function								
	Power on Indication	Fault Indication	Display Fault Condition Values	Service Interval Indication	Service Countdown Timers	Configurable Alarm Settings	Remote Volt Free Alarm Contacts	Filter Service Timer	DDS Energy Management System
AX_S	•	•		•			•		
AX_SDS					•				
AX_E			•			•		•	•

*ATEX compliant option available. For hazardous environments, a fully pneumatic ATEX compliant version of AX Series is available.
ATEX Directive 94/9/EC, Group II, Category 2GD, T6.

Correction Factors

Temperature Correction Factor CFT							
Maximum Inlet Temperature	[°C]	25	30	35	40	45	50
	[°F]	77	86	95	104	113	122
	CFT	1.00	1.00	1.00	1.04	1.14	1.37


Pressure Correction Factor CFP											
Minimum Inlet Pressure	[bar g]	4	5	6	7	8	9	10	11	12	13
	[psi g]	58	73	87	100	116	131	145	160	174	189
	CFP	1.60	1.33	1.14	1.00	0.89	0.80	0.73	0.67	0.62	0.57

Dewpoint Correction Factor CFD		Option 2	Standard	Option 1
Required Dewpoint	PDP °C	-20	-40	-70
	PDP °F	-4	-40	-100
	CFD	0.91	1.00	1.43

Weights and Dimensions

Model	Pipe Size	Dimensions						Weight	
		Height [H]		Width [W]		Depth [D]		[kg]	[lbs]
		[mm]	[ins]	[mm]	[ins]	[mm]	[ins]		
A068XS	2"	1647	64.8	687	27.0	550	21.7	235	518
A102XS				856	33.7			316	696
A127XS								355	782
A170XS				1025	40.3			450	992
A212XS	2½"	1892	74.5	1194	47.0			543	1197
A255XS				1363	53.6	637	1404		
A297XS				1532	60.3	731	1611		
A340XS				1701	67.0	825	1818		

A068XS - A340XS



Inlet High Efficiency Filter and Outlet Dust Filter are included with these dryers as standard.

Recommended Filtration

For Dryer Model	Filter Pipe Size BSPT or NPT	Inlet General Purpose Pre-filter	Inlet High Efficiency Filter	Outlet Dust Filter
A068XS	2"	CF0132G 2"G	CF0132G 2"H	CF0132G 2"G
A102XS				
A127XS				
A170XS				
A212XS	2½"	CF0258G2 ½"G	CF0258G2 ½"H	CF0258G2 ½"G
A255XS				
A297XS				
A340XS				

Global experience – truly local service

With over 200 years of engineering excellence, the CompAir brand offers an extensive range of highly reliable, energy efficient compressors and accessories to suit all applications.

An extensive network of dedicated CompAir sales companies and distributors across all continents provide global expertise with a truly local service, ensuring our advanced technology is backed up with the right support.

As part of the worldwide Gardner Denver operation, CompAir has consistently been at the forefront of compressed air systems development, culminating in some of the most energy efficient and low environmental impact compressors on the market today, helping customers achieve or surpass their sustainability targets.



CompAir compressed air product range

Advanced Compressor Technology Lubricated

- Rotary Screw
 - > Fixed and Regulated Speed
- Piston
- Portable

Oil-Free

- Water Injected Screw
 - > Fixed and Regulated Speed
- Two Stage Screw
 - > Fixed and Regulated Speed
- Piston
- High Speed Centrifugal - Quantima®

Complete Air Treatment Range

- Filter
- Refrigerant and Desiccant Dryer
- Condensate Management
- Heat of Compression Dryer
- Nitrogen Generator

Modern Control Systems

- CompAir DELCOS Controllers
- SmartAir Master Sequencer

CompAir policy is one of continuous improvement and we therefore reserve the right to alter specifications and prices without prior notice. All products are sold subject to the Company's conditions of sale.

Value Added Services

- Professional Air Audit
- Performance Reporting
- Leak Detection

Leading Customer Support

- Custom Engineered Solutions
- Local Service Centres
- Genuine CompAir Parts and Lubricants

www.compair.com sales@compair.com